

VX-350 SERIES

VHF/UHF Portable Radios



- 16 CHANNEL CAPACITY
- POWER OUTPUT : 5 W / 1 W (SELECTABLE)
- WIDE BAND COVERAGE
 - VHF 134-174 MHz
 - UHF 400-470 MHz / 450-512 MHz
- 8-CHARACTER ALPHANUMERIC DISPLAY (VX-354)
- 500 mW LOUD AUDIO WITH LARGE 1.4" SPEAKER
- LARGE CAPACITY 2000 mAh LI-ION BATTERY (FNB-V96LI)
- LONG BATTERY LIFE MORE THAN 15 HOURS* WITH RX/TX BATTERY SAVER CIRCUIT
- COMPACT AND RUGGED CONSTRUCTION
- WIDE/NARROW BANDWIDTH PER CHANNEL
- CTCSS / DCS ENCODE AND DECODE
- DTMF ANI
- 2-TONE ENCODE AND DECODE
- 5-TONE SIGNALING BUILT-IN
- EMERGENCY FEATURE
- VERSATILE SCAN (PRIORITY, DUAL WATCH, FOLLOW-ME AND TA SCAN)
 - LONE WORKER FEATURE BUILT IN
 - STUN, KILL, REVIVE AND REMOTE LISTEN
 - ARTS™ (AUTO-RANGE TRANSPOND SYSTEM)
 - DTMF PAGING (OPTION)
 - ENCRYPTION (OPTION)
 - VOICE INVERSION
 - ROLLING CODE
 - MDC 1200® / GE-STAR® ANI (OPTION)
 - PC PROGRAMMING
 - RADIO-TO-RADIO CLONING

*FNB-V96LI/5-5-90 duty cycle w/saver



VX-354

Actual Size



VX-351



•Top



•Side

VX-350 SERIES VHF/UHF Portable Radio

LONG BATTERY LIFE MORE THAN 15 HOURS WITH 2000 mAh LI-ION BATTERY FNB-V96LI

The VX-350 Portables may be equipped with advanced FNB-V96LI Lithium-Ion Battery Packs with 2000 mAh of capacity, for operating times of more than 15 hours, even when using 5 Watts (5-5-90 duty cycle, w/saver).

Battery	Saver ON (RX:STBY 1:4)	Saver OFF
FNB-V96LI 2000mAh	15.5 (15) hrs	13 (12.5) hrs
FNB-V95LI 1800 mAh	14 (13.5) hrs	11.7 (11.3) hrs

() : UHF version

WIDE BANDWIDTH

For communicating with other agencies, companies, or even within your own communications system, the wide bandwidth of this radio will let you operate anywhere within the 40 MHz (VHF) or 62 MHz (UHF) band.

8-CHARACTER ALPHANUMERIC DISPLAY (VX-354)

Providing indication of either the channel number or an Alphanumeric Channel Label of up to 8 characters, the LCD display also provides convenient operation function icons to provide instant recognition of radio status. Including signal strength indicator and battery gauge.

500 mW LOUD AUDIO WITH LARGE 1.4" SPEAKER

Ideal for reception in noisy environments, the VX-350's high-powered audio is coupled to a large 1.4" internal speaker, assuring solid copy throughout difficult crowd control, fire, or sporting-event operations.

COMPACT AND RUGGED CONSTRUCTION

Weighing just 11 oz and measuring just 2.3" x 4.1" x 1.3" (WHD) the VX-350 is ideal for business, industry, and public safety applications where light weight and compact size are important.

WIDE/NARROW BANDWIDTH PER CHANNEL

When programming radios for use in different jurisdictions, the VX-350 Series portables may be set up, channel by channel, for use in 12.5 kHz, 20 kHz, or 25 kHz channel spacing environments. Deviation and bandwidth are automatically set according to the configuration you choose.

BUILT-IN EMERGENCY FEATURE

With the built-in emergency feature, you are never alone. Any softkey can be programmed for Emergency operation. When activated, the radio will go to a designated channel, broadcast the unit ID and transmit live audio for pre-determined intervals.

2-TONE ENCODE AND DUAL 2-TONE DECODE

The VX-350 Series can transmit a 2-Tone paging call, and can receive 2-Tone calls using different tone combinations. For advanced network or fleet operations, a 5-Tone Encoder-Decoder circuit is included in the VX-350 Series.

DTMF ANI

A DTMF Automatic Number Identification string may be programmed into the VX-350, providing the dispatcher with a multiple-digit confirmation of the transmitting portable's identity.

DTMF PAGING (OPTION)

The optional FVP-25 board adds a DTMF paging decoder. With DTMF you can Stun, Kill and Alert.

ENCRYPTION (OPTION) VOICE INVERSION, ROLLING CODE

The FVP-35 and FVP-36 Encryption Units provide security for your important public safety and security communications. A DTMF Paging function is also included in the FVP-25 module, for selective calling.

MDC-1200® / GE-STAR® ANI ENCODE (OPTION)

Automatic Number Identification, triggered by the pressing of the PTT key, is available in the most popular industry-standard formats, via the optional VME-100.

OTHER FEATURES

- VERSATILE SCAN (PRIORITY, DUAL WATCH, FOLLOW-ME AND TA SCAN)
- CTCSS / DCS ENCODE AND DECODE
- ARTS™ (AUTO-RANGE TRANSPOND SYSTEM)
- WHISPER
- PC PROGRAMMING
- RADIO-TO-RADIO CLONING

Applicable MIL-STD (Pending)

Standard	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.2/Procedure I, II	500.2/Procedure I, II	500.3/Procedure I, II
High Temperature	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Rain	506.2/Procedure II	506.3/Procedure I	506.4/Procedure I, III
Humidity	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.2	509.3	509.4
Dust	510.2/Procedure I	510.3/Procedure I	510.4/Procedure III
Vibration	514.3/Procedure Cat. 10	514.4/Procedure Cat. 10	514.5/Procedure Cat. 24
Shock	516.3/Procedure I	516.4/Procedure I	516.5/Procedure I

Specifications

	VHF	UHF
General Specification		
Frequency Range	134 -174 MHz	400 - 470 MHz 450 - 512 MHz
Number of Channels	16	
Power Supply Voltage	7.4 V DC ±20 %	
Channel Spacing	12.5/20/25 kHz	
Battery Life (5-5-90 duty) w/FNB-V96LI (2000mAh)	15.5 hrs (13 hrs w/o saver)	15 hrs (12.5 hrs w/o saver)
Operating Temperature Range	-22° F to 140° F (-30° C to +60° C)	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohm	
Dimension (W x H x D)	2.3" x 4.1" x 1.3" (58 x 105 x 33 mm)	
Weight (Approx.)	10.9 oz (310 g)(w/FNB-V96LI, Antenna, Belt Clip)	

	VHF	UHF
Receiver Specification	measured by TIA/EIA-603	
Sensitivity (12dB SINAD)	0.25 μV	0.25 μV
Adjacent Channel Selectivity	65 / 60 dB (25 kHz/12.5 kHz)	
Intermodulation	65 / 60 dB (25 kHz/12.5 kHz)	
Spurious and Image Rejection	65 dB	
Audio Output	500 mW @ 4 ohms 10 % THD	
Transmitter Specification	measured by TIA/EIA-603	
Output Power	5 / 1 W	5 / 1 W
Modulation	16K0F3E, 11K0F3E	
Conducted Spurious Emission	65 dB below carrier	
FM Hum & Noise	45 / 40 dB (25 kHz/12.5 kHz)	
Audio Distortion	< 3 % @1kHz	

Specification may be changed without notification.

Accessories & Options

 MH-45B4B Noise Canceling Speaker Microphone	 MH-450S Speaker Microphone	 MH-360S Compact Speaker Microphone	 MH-37A4B Earpiece Microphone	 VC-25 VOX Headset	 FVP-25 Encryption / DTMF Paging Unit	 VME-100 MDC-1200®/GE-STAR® ANI Encode Unit	 FVP-36 Voice Inversion Encryption Unit	 FVP-35 Rolling Code Encryption Unit									
 FNB-V96LI 7.4 V 2000mAh Hi-Spec Li-Ion Battery Pack	 FNB-V95LI 7.4 V 1800mAh Standard Li-Ion Battery Pack	 VAC-300B/C/F* Desktop Rapid Charger (CD-34 + PA-42 B/C/F*)	 VAC-6300 Gunit Multi Rapid Charger	 VCM-2 Vehicle Charger Mount Adaptor	 DCM-1 Desktop Charger Mounting Adapter for VAC-10	 CT-27 Cloning Cable (Radio to Radio Cloning)	<table border="1"> <tr> <td>Programming Cable</td> <td>USB</td> <td>FIF-10/A + CT-106</td> </tr> <tr> <td></td> <td>RS-232C</td> <td>CT-29 + CT-28</td> </tr> <tr> <td>Programming Software</td> <td colspan="2">CE86</td> </tr> </table>	Programming Cable	USB	FIF-10/A + CT-106		RS-232C	CT-29 + CT-28	Programming Software	CE86		
Programming Cable	USB	FIF-10/A + CT-106															
	RS-232C	CT-29 + CT-28															
Programming Software	CE86																

LCC-350 Leather Case *B for 120 VAC, C for 230 VAC, F for 220 VAC Various accessories listed may not be available in some countries.

ANTENNA LIST

UHF	ATU-6A	400-430 MHz	ATU-6DS	450-485 MHz/3.5"
	ATU-6D	450-490 MHz	ATU-6F	490-512 MHz
VHF	ATV-6A	134-151 MHz/3.5"	ATV-10A	145-155 MHz HIGH GAIN
	ATV-6B	150-163 MHz/3.5"	ATV-10B	150-160 MHz HIGH GAIN
	ATV-6C	161-174 MHz/3.5"	ATV-10C	155-165 MHz HIGH GAIN
	ATV-6XL	VHF UNTUNED	ATV-10E	165-175 MHz HIGH GAIN
	ATV-8A	134-151 MHz		
	ATV-8B	150-163 MHz		
	ATV-8C	161-174 MHz		



Vertex Standard US Headquarters

10900 Walker Street, Cypress, CA 90630, U.S.A.
Phone 714/827-7600; Fax 714/827-8100
<http://www.vertexstandard.com>

Communications
Electronics
2617 Palmer Rd
Hebron, Ohio
740-929-2500